

BNCI Horizon 2020

The Future of Brain/Neural Computer Interaction: Horizon 2020

Appendix References

BNCI Horizon 2020 (FP7-ICT-2013-10 609593) was funded by the
European Commission within the 7th Framework Programme.
Project runtime: Nov 2013–Apr 2015

This appendix and the corresponding main document can be downloaded from
<http://bnci-horizon-2020.eu/>



References Appendix

Ahn, M., Lee, M., Choi, J., and Jun, S. C. (2014). A review of brain-computer interface games and an opinion survey from researchers, developers and users. *Sensors* 14, 14601–14633. doi:10.3390/s140814601.

Allison, B. Z., Brunner, C., Altstätter, C., Wagner, I. C., Grissmann, S., and Neuper, C. (2012a). A hybrid ERD/SSVEP BCI for continuous simultaneous two dimensional cursor control. *J Neurosci Methods* 209: 299–307. doi:10.1016/j.jneumeth.2012.06.022.

Allison, B. Z., Brunner, C., Kaiser, V., Müller-Putz, G. R., Neuper, C., and Pfurtscheller, G. (2010). Toward a hybrid brain-computer interface based on imagined movement and visual attention. *J Neural Eng* 7(2): 026007. doi:10.1088/1741-2560/7/2/026007.

Allison, B. Z., Leeb, R., Brunner, C., Müller-Putz, G. R., Bauernfeind, G., Kelly, J. W., and Neuper, C. (2012b). Toward smarter BCIs: extending BCIs through hybridization and intelligent control. *J Neural Eng* 9: 13001. doi: 10.1088/1741-2560/9/1/013001.

Aloise, F., Aricò, P., Schettini, F., Salinari, S., Mattia, D., and Cincotti, F. (2013). Asynchronous gaze-independent event-related potential-based brain-computer interface. *Artif. Intell. Med.* 59, 61–69. doi:10.1016/j.artmed.2013.07.006.

Amiri, S., Fazel-Rezai, R., and Asadpour, V. (2013). A review of hybrid brain-computer interface systems. *Adv Hum-Comp Int* 2013: 1–8.

Andersson, P., Pluim, J.P., Siero, J.C., Klein, S., Viergever, M. A., and Ramsey N.F. (2011). Real-time decoding of brain responses to visuospatial attention using 7T fMRI. *PLoS One* 6: e27638. doi:10.1371/journal.pone.0027638.

Attiah, M. A., and Farah, M. J. (2014). Minds, motherboards, and money: futurism and realism in the neuroethics of BCI technologies. *Front. Syst. Neurosci.* 8, 86. doi:10.3389/fnsys.2014.00086.

Baillet S (2011) Electromagnetic brain Mapping using MEG and EEG. In: Decety J, Cacioppo J (eds) *The Oxford Handbook of Social Neuroscience*. Oxford University Press. pp 97-133.

Bansal, A. K., Trucculo, W., Vargas-Irwin, C. E., and Donoghue J.P. (2012). Decoding 3D reach and grasp from hybrid signals in motor and premotor cortices: spikes, multiunit activity, and local field potentials. *J Neurophysiol* 107: 1337-1355. doi:10.1152/jn.00781.2011.

Belda-Lois, J.-M., Mena-del Horno, S., Bermejo-Bosch, I., Moreno, J. C., Pons, J. L., Farina, D., Iosa, M., Molinari, M., Tamburella, F., Ramos, A., et al. (2011). Rehabilitation of gait after stroke: a review towards a top-down approach. *J Neuroeng Rehabil* 8, 66. doi:10.1186/1743-0003-8-66.

Berger, T. W., Chapin, J. K., Gerhardt, G. A., McFarland, D. J., Principe, J. C., Soussou, W. V., Taylor, D. M., and Tresco P. A. (2007). WTEC Panel Report on International assessment of research and development in brain-computer interfaces.

Bishop W, Chestek CC, Gilja V, Nuyujukian P, Foster JD, Ryu SI, Shenoy KV, anf Yu BM (2014) Self-recalibrating classifiers for intracortical brain-computer interfaces. *J Neural Eng* 11: 026001.

- Blain-Moraes, S., Schaff, R., Gruis, K. L., Huggins, J. E., and Wren, P. A. (2012). Barriers to and mediators of brain-computer interface user acceptance: focus group findings. *Ergonomics* 55, 516–525. doi:10.1080/00140139.2012.661082.
- Blakely, T., Miller, K.J., Zanos, S.P., Rao, R.P., and Ojemann, J.G. (2009). Robust, long-term control of an electrocorticographic brain-computer interface with fixed parameters. *Neurosurg Focus* 27: E13. doi:10.3171/2009.4.FOCUS0977.
- Blankertz, B., Lemm, S., Treder, M., Haufe, S., and Müller, K.R. (2011). Single-trial analysis and classification of ERP components—a tutorial. *NeuroImage* 56: 814-825. doi:10.1016/j.neuroimage.2010.06.048.
- Blankertz, B., Tangermann, M., Vidaurre, C., Fazli, S., Sannelli, C., Haufe, S., Maeder, C., Ramsey, L., Sturm, I., Curio, G., et al. (2010). The Berlin Brain-Computer Interface: Non-Medical Uses of BCI Technology. *Front. Neurosci.* 4, 198. doi:10.3389/fnins.2010.00198.
- Blankertz, B., Tomioka, R., Lemm, S., Kawanabe, M., and Müller, K.R. (2008). Optimizing spatial filters for robust EEG single-trial analysis. *IEEE Signal Process Mag* 25: 41-56. doi:10.1109/MSP.2008.4408441
- Boas, D.A., Elwell, C.A., Ferrari, M., and Taga, G. (2014). Twenty years of functional near-infrared spectroscopy: introduction for the special issue, *NeuroImage* 85: 1–5. doi:10.1016/j.neuroimage.2013.11.033.
- Brunner, C., Andreoni, G., Bianchi, L., Blankertz, B., Breitwieser, C., Kanoh, S., Kothe, C.A., Lécuyer, A., Makeig, S., Mellinger, J., Perego, P., Renard, Y., Schalk, G., Susila, I.P., Venthur, B., and Müller-Putz, G.R. (2013). BCI software platforms. In: Allison BZ, Dunne S, Leeb R, Del R Millan J, Nijholt A (eds) *Towards practical brain-computer interfaces*. Springer Berlin Heidelberg. pp 303-331.
- Brunner, P., Bianchi, L., Guger, C., Cincotti, F., and Schalk, G. (2011). Current trends in hardware and software for brain-computer interfaces (BCIs). *J Neural Eng* 8. doi:10.1088/1741-2560/8/2/025001.
- Brunner, P., Ritaccio, A.L., Emrich, J.F., Bischof, H., and Schalk, G. (2011). Rapid communication with a 'P300' matrix speller using electrocorticographic signals (ECoG). *Front Neurosci* 7: 5. doi:10.3389/fnins.2011.00005.
- Buch, E., Weber, C., Cohen, L.G., Braun, C., Dimyan, M.A., Ard, T., Mellinger, J., Caria, A., Soekadar, S., Fourkas, A., and Birbaumer, N. (2008). Think to move: a neuromagnetic brain-computer interface (BCI) system for chronic stroke. *Stroke* 39: 910-917. doi: 10.1161/STROKEAHA.107.505313.
- Budde, J., Shajan, G., Scheffler, K., and Pohmann, R. (2014). Ultra-high resolution imaging of the human brain using acquisition-weighted imaging at 9.4 T. *NeuroImage* 86: 592-598. doi:10.1016/j.neuroimage.2013.08.013.
- Carabalona, R., Castiglioni, P., and Gramatica, F. (2009). Brain-computer interfaces and neurorehabilitation. *Stud. Health Technol. Inform.* 145, 160–176.
- Carabalona, R., Grossi, F., Tessadri, A., Castiglioni, P., Caracciolo, A., and de Munari, I. (2012). Light on! Real world evaluation of a P300-based brain-computer interface (BCI) for environment control in a smart home. *Ergonomics* 55, 552–563. doi:10.1080/00140139.2012.661083.

Carlson, T, and Millán JdR (2013). Brain-controlled wheelchairs: A robotic architecture. *IEEE Rob Aut Mag* 20: 65-73. doi:10.1109/MRA.2012.2229936

Carlson, T., Tonin, L., Perdakis, S., Leeb, R., and Millan, J. del R. (2013). A hybrid BCI for enhance control of a telepresence robot. *Conf Proc IEEE Eng Med Biol Soc* 2013: 3097-3100. doi:10.1109/EMBC.2013.6610196.

Carmichael, C., and Carmichael, P. (2014). BNCI systems as a potential assistive technology: ethical issues and participatory research in the BrainAble project. *Disabil. Rehabil. Assist. Technol.* 9, 41–47. doi:10.3109/17483107.2013.867372.

Chao, Z.C., Nagsaka, Y., and Fuji, N. (2010). Long-term asynchronous decoding of arm motion using electrocorticographic signals in monkeys. *Front Neuroeng* 30:3. doi:10.3389/fneng.2010.00003.

Charvet, G., Sauter-Starace, F., Foerster, M., Ratel, D., Chabrol, C., Porcherot, J., Robinet, S., Reverdy, J, D'Errico, R., Mestais, C., and Benabid, A.L. (2013). WIMAGINE: 64-channel ECoG recording implant for human applications. *Conf Proc IEEE Eng Med Biol Soc* 2013: 2756-2759.

Chestek CA, Gilja V, Nuyujukian P, Foster JD, Fan JM, Kaufman MT, Churchland MM, Rivera-Alvidrez Z, Cunningham JP, Ryu SI, Shenoy KV (2011) Long-term stability of neural prosthetic control signals from silicon cortical arrays in rhesus macaque motor cortex. *J Neural Eng* 8: 045005. doi:10.1088/1741-2560/8/4/045005.

Chestek, C.A., Gilja, V., Nuyujukian, P., Kier, R.J., Solzbacher, F., Ryi, S.I., Harrison, R.R., Shenoy, K.V. (2009). HermesC: low-power wireless neural recording system for freely moving primates. *IEEE Trans Neural Syst Rehabil Eng* 17: 330-338. doi:10.1109/TNSRE.2009.2023293.

Clausen, J. (2011). Conceptual and ethical issues with brain-hardware interfaces. *Curr. Opin. Psychiatry* 24, 495–501. doi:10.1097/YCO.0b013e32834bb8ca.

Combaz, A., Chatelle, C., Robben, A., Vanhoof, G., Goeleven, A., Thijs, V., Van Hulle, M. M., and Laureys, S. (2013). A comparison of two spelling Brain-Computer Interfaces based on visual P3 and SSVEP in Locked-In Syndrome. *PloS One* 8, e73691. doi:10.1371/journal.pone.0073691.

Cui, X., Bray, S., Bryant, D.M., Glover, G.H., and Reiss, A.L. (2011). A quantitative comparison of NIRS and fMRI across multiple cognitive tasks. *NeuroImage* 5: 2808-2821. doi:10.1016/j.neuroimage.2010.10.069.

Dal Seno, B., Matteucci, M., and Mainardi, L.T. (2010). The utility metric: a novel method to assess the overall performance of discrete brain-computer interfaces. *IEEE Trans Neural Syst Rehabil Eng* 18: 20–28. doi:10.1109/TNSRE.2009.2032642.

Dangi, S., Gowda, S., and Carmena, J.M. (2013). Likelihood gradient ascent (LGD): A closed-loop decoder adaptation algorithm for brain-machine interfaces. *Conf Proc IEEE Eng Med Biol Soc* 2013: 2768-2771. doi:10.1109/EMBC.2013.6610114.

Dimyan, M. A., and Cohen, L. G. (2011). Neuroplasticity in the context of motor rehabilitation after stroke. *Nat Rev Neurol* 7, 76–85. doi:10.1038/nrneurol.2010.200.

- Do, A.H., Wang, P.T., King, C.E., Schombs, A., Lin J.J., Sazgar, M., Hsu, F.P., Shaw, S.J., Millett, D.E., Liu, C.Y., Szymanska, A.A., Chui, L.A., and Nenadic, Z. (2013). Sensitivity and specificity of upper extremity movements decoded from electrocorticogram. *Conf Proc IEEE Eng Med Biol Soc* 2013: 5618-5621. doi:10.1109/EMBC.2013.6610824.
- Ekdandem, J. I., Davis, T. A., Alvarez, I., James, M. T., and Gilbert, J. E. (2012). Evaluating the ergonomics of BCI devices for research and experimentation. *Ergonomics* 55, 592–598. doi:10.1080/00140139.2012.662527.
- Elsner, B., Kugler, J., Pohl, M., and Mehrholz, J. (2013). Transcranial direct current stimulation (tDCS) for improving aphasia in patients after stroke. *Cochrane Database Syst Rev* 6, CD009760. doi:10.1002/14651858.CD009760.pub2.
- Evers, K., and Sigman, M. (2013). Possibilities and limits of mind-reading: a neurophilosophical perspective. *Conscious. Cogn.* 22, 887–897. doi:10.1016/j.concog.2013.05.011.
- Fatourechi, M., Bashashati, A., Ward, R.K., Birch, G.E. (2007). EMG and EOG artifact in brain computer interface systems: A survey. *Clin Neurophysiol* 118: 480-494.
- Fazel-Rezai, R., Allison, B. Z., Guger, C., Sellers, E. W., Kleih, S. C., and Kübler, A. (2012). P300 brain computer interface: current challenges and emerging trends. *Front. Neuroengineering* 5, 14. doi:10.3389/fneng.2012.00014.
- Fazli, S., Mehnert, J., Steinbrink, J., Curio, G., Villringer, A., Müller, K-R., and Blankertz, B. (2011). Enhanced performance by a hybrid NIRS-EEG brain computer interface. *NeuroImage* 59: 519–529. doi:10.1016/j.neuroimage.2011.07.084.
- Fazli, S., Mehnert, J., Steinbrink, J., Curio, G., Villringer, A., Müller, K.R., Blankertz, B (2012). Enhanced performance by a hybrid NIRS–EEG brain computer interface. *NeuroImage* 59: 519-529. doi:10.1016/j.neuroimage.2011.07.084.
- Federici, S., and Scherer, M. (2012). *Assistive Technology Assessment Handbook*. CRC Press.
- Felton, E. A., Williams, J. C., Vanderheiden, G. C., and Radwin, R. G. (2012). Mental workload during brain-computer interface training. *Ergonomics* 55, 526–537. doi:10.1080/00140139.2012.662526.
- Fernando Nicolas-Alonso, and L., Gomez-Gil, J. (2012). Brain computer interfaces, a review. *Sensors* 12: 1211–1279.
- Ferrari, M., and Quaresima, V. (2012). A brief review on the history of human functional near-infrared spectroscopy (fNIRS) development and fields of application. *NeuroImage* 63: 921–935. doi:10.1016/j.neuroimage.2012.03.049.
- Flöel, A. (2014). tDCS-enhanced motor and cognitive function in neurological diseases. *Neuroimage* 85 Pt 3, 934–947. doi:10.1016/j.neuroimage.2013.05.098.
- Fonseca, C., Cunha, J.P.S., Martins, R.E., Ferreira, V.M., de Sa, J.P.M., Barbosa, M.A., and da Silva, A.M. (2007). A novel dry active electrode for EEG recording. *IEEE Trans Biomed Eng* 54: 162–165.

- Friedrich, E. V. C., Neuper, C., and Scherer, R. (2013a). Whatever works: a systematic user-centered training protocol to optimize brain-computer interfacing individually. *PloS One* 8, e76214. doi:10.1371/journal.pone.0076214.
- Friedrich, E. V. C., Scherer, R., and Neuper, C. (2013b). Long-term evaluation of a 4-class imagery-based brain-computer interface. *Clin. Neurophysiol. Off. J. Int. Fed. Clin. Neurophysiol.* 124, 916–927. doi:10.1016/j.clinph.2012.11.010.
- Georgopoulos, A.P., Kalaska, J.F., Caminiti, R., and Massey J.T. (1982). On the relations between the direction of two-dimensional arm movements and cell discharge in primate motor cortex. *J Neurosci* 2: 1527-1537.
- Gilja, V., Chestek, C.A., Henderson, J.M., Deisseroth, K., Shenoy, K.V. (2011). Challenges and opportunities for next-generation intracortically based neural prostheses. *IEEE Trans Biomed Eng* 58: 1891-1899. doi:10.1109/TBME.2011.2107553.
- Gilja, V., Nuyujukian, P., Chestek, C.A., Cunningham, J.P., Yu, B.M., Fan, J.M., Ryu, S.I., Shenoy, K.V. (2012). A brain machine interface control algorithm designed from a feedback control perspective. *Conf Proc IEEE Eng Med Biol Soc 2012*: 1318-1322. doi:10.1109/EMBC.2012.6346180.
- Glannon, W. (2014). Neuromodulation, agency and autonomy. *Brain Topogr.* 27, 46–54. doi:10.1007/s10548-012-0269-3.
- Grosse-Wentrup, M., and Schölkopf, B. (2013). A review of performance variations in SMR-based brain-computer interfaces (BCIs). In: Guger C, Allison BZ, Edlinger G (eds) *Brain-Computer Interface Research*. SpringerBriefs in electrical and computer engineering. Springer Berlin Heidelberg. pp. 39–51
- Grosse-Wentrup, M., Mattia, D., and Oweiss, K. (2011). Using brain-computer interfaces to induce neural plasticity and restore function. *J Neural Eng* 8. doi:10.1088/1741-2560/8/2/025004.
- Grübler, G., Al-Khodairy, A., Leeb, R., Pisotta, I., Riccio, A., Rohm, M., and Hildt, E. (2014). Psychosocial and Ethical Aspects in Non-Invasive EEG-Based BCI Research—A Survey Among BCI Users and BCI Professionals. *Neuroethics* 7, 29–41. doi:10.1007/s12152-013-9179-7.
- Grychtol, B., Lakany, H., Valsan, G., and Conway, B. A. (2010). Human behavior integration improves classification rates in real-time BCI. *IEEE Trans. Neural Syst. Rehabil. Eng. Publ. IEEE Eng. Med. Biol. Soc.* 18, 362–368. doi:10.1109/TNSRE.2010.2053218.
- Gürkök, H., and Nijholt, A. (2012). Brain-computer interfaces for multimodal interaction: A survey and principles. *Int J Hum Comput Interact*, 28(5), 292-307.
- Hansen, P.C., Kringelbach, R., Salmelin R. (eds) (2010) *MEG - An introduction to methods*. Oxford University Press, 2010.
- Hart, S. G., and Staveland, L. E. (1988). “Development of NASA-TLX (Task Load Index): Results of Empirical and Theoretical Research,” in *Advances in Psychology Human Mental Workload.*, ed. Peter A. Hancock and Najmedin Meshkati (North-Holland), 139–183.

Haselager, P., Vlek, R., Hill, J., and Nijboer, F. (2009). A note on ethical aspects of BCI. *Neural Netw. Off. J. Int. Neural Netw. Soc.* 22, 1352–1357. doi:10.1016/j.neunet.2009.06.046.

Henle, C., Raab, M., Cordeiro, J.G., Doostkam, S., Schulze-Bonhage, A., Stieglitz, T., Rickert, J. (2011). First long term in vivo study on subdurally implanted micro-ECoG electrodes, manufactured with a novel laser technology. *Biomed Microdevices* 13: 59-68. doi:10.1007/s10544-010-9471-9.

Hillman, E.M.C. (2014). Coupling mechanism and significance of the BOLD signal: A status report. *Ann Rev Neurosci* 37. doi:10.1146/annurev-neuro-071013-014111.

Hochberg, L.R., Bacher, D., Jarosiewicz, B., Massa, N.Y., Simeral, J.D., Vogel, J., Haddadin, S., Liu, J., Cash, S.S., van der Smagt, P., Donoghue, J.P. (2012). Reach and grasp by people with tetraplegia using a naturally controlled robotic arm. *Nature* 485: 372-375. doi:10.1038/nature11076.

Hochberg, L.R., Serruya, M.D., Friehs, G.M., Mukand, J.A., Saleh, M., Caplan, A.H., Branner, A. (2006). Neuronal ensemble control of prosthetic devices by a human with tetraplegia. *Nature* 442: 164-171.

Höhne, J., Schreuder, M., Blankertz, B., and Tangermann, M. (2011). A Novel 9-Class Auditory ERP Paradigm Driving a Predictive Text Entry System. *Front. Neurosci.* 5, 99. doi:10.3389/fnins.2011.00099.

Holz, E. M., Höhne, J., Staiger-Sälzer, P., Tangermann, M., and Kübler, A. (2013). Brain-computer interface controlled gaming: evaluation of usability by severely motor restricted end-users. *Artif. Intell. Med.* 59, 111–120. doi:10.1016/j.artmed.2013.08.001.

Homer, M.L., Nurmikko, A.V., Donoghue, J.P., Hochberg, L.R. (2013). Sensors and decoding for intracortical brain computer interfaces. *Annu Rev Biomed Eng* 15: 383-405. doi:10.1146/annurev-bioeng-071910-124640.

<http://nextbigfuture.com/2013/01/telepresence-robots-from-350-to-16000.html>

<http://www.asha.org/public/hearing/Cochlear-Implant-Frequently-Asked-Questions/>

<http://www.stroke.org>

Huggins, J. E., Wren, P. A., and Gruis, K. L. (2011). What would brain-computer interface users want? Opinions and priorities of potential users with amyotrophic lateral sclerosis. *Amyotroph. Lateral Scler. Off. Publ. World Fed. Neurol. Res. Group Mot. Neuron Dis.* 12, 318–324. doi:10.3109/17482968.2011.572978.

Hwang, H.J., Kim, S., Choi, S., Im, C.H. (2013). EEG-based Brain computer interfaces: a thorough literature survey. *Int J Hum-Comp Int* 29: 814-826.

ISO 9241-210:2010, Ergonomics of human-system interaction - Part 210: Human-centred design for interactive systems. Multiple. Distributed through American National Standards Institute.

Kaufmann, T., Herweg, A., Kübler A. (2014). Toward brain-computer interface based wheelchair control utilizing tactually-evoked event-related potentials. *J Neuroeng Rehabil* 11: 1-17. doi:10.1186/1743-0003-11-7.

Kaufmann, T., Schulz, S.M., Gruenzinger, C, Kuebler ,A. (2011). Flashing characters with famous faces improves ERP-based brain-computer interface performance. *J Neural Eng* 8: 056016. doi:10.1088/1741-2560/8/5/056016.

Kim, B.H., Kim M., Sungho J. (2014). Quadcopter flight control using a low-cost hybrid interface with EEG-based classification and eye-tracking. *Comput Biol Med* 51: 82-92. doi:10.1016/j.combiomed.2014.04.020.

Kindermans, P.J., Tangermann, M., Müller, K.R., Schrauwen, B (2014). Integrating dynamic stopping, transfer learning and language models in an adaptive zero-training ERP speller. *J Neural Eng* 11: 035005. doi:10.1088/1741-2560/11/3/035005.

Kitzinger, J. (1995). Qualitative research. Introducing focus groups. *BMJ* 311, 299–302.

Kotchetkov, I. S., Hwang, B. Y., Appelboom, G., Kellner, C. P., and Connolly, E. S., Jr (2010). Brain-computer interfaces: military, neurosurgical, and ethical perspective. *Neurosurg. Focus* 28, E25. doi:10.3171/2010.2.FOCUS1027.

Krusienski, D.J., Sellers, E.W., McFarland, D.J., Vaughan, T.M., Wolpaw, J.R. (2008). Toward enhanced P300 speller performance. *J Neurosci Methods* 167: 15-21.

Kubaneck, J., Miller, K.J., Ojemann, J.G, Wolpaw, J.R., Schalk, G. (2009). Decoding flexion of individual fingers using electrocorticographic signals in humans. *J Neural Eng* 6: 066001.

Kubler, A., Holz, E., Kaufmann, T., and Zickler, C. (2013). “A User Centred Approach for Bringing BCI Controlled Applications to End-Users,” in *Brain-Computer Interface Systems - Recent Progress and Future Prospects*, ed. R. Fazel-Rezai (InTech).

Kübler, A., Zickler, C., Holz, E., Kaufmann, T., Riccio, A., and Mattia, D. (2013). Applying the user-centred design to evaluation of Brain-Computer Interface controlled applications. *Biomed. Eng. Biomed. Tech.* .

Lee B, Liu CY, Apuzzo MLJ (2013) A primer on brain-machine interfaces, concepts, and technology: A key element in the future of functional neurorestoration. *World Neurosurg* 79: 457-471.

Lee, B. B., Cripps, R. A., Fitzharris, M., and Wing, P. C. (2014). The global map for traumatic spinal cord injury epidemiology: update 2011, global incidence rate. *Spinal cord*, 52(2), 110-116. doi: 10.1038/sc.2012.

Lee, T.-S., Goh, S. J. A., Quek, S. Y., Phillips, R., Guan, C., Cheung, Y. B., Feng, L., Teng, S. S. W., Wang, C. C., Chin, Z. Y., et al. (2013). A brain-computer interface based cognitive training system for healthy elderly: a randomized control pilot study for usability and preliminary efficacy. *PloS One* 8, e79419. doi:10.1371/journal.pone.0079419.

Leeb, R., Lancelle, M., Kaiser, V., Fellner, D.W., Pfurtscheller, G. (2013). Thinking penguin: Multi-modal brain-computer interface control of a VR game. *IEEE T Comp Intel AI* 5: 117-128.

Leeb, R., Millán JdR. (2012). Introduction to devices, applications and users: Towards practical BCIs based on shared control techniques. In: Allison BZ, Dunne S, Leeb R, Del R Millan J, Nijholt A (eds) *Towards practical brain-computer interfaces*. Springer Berlin Heidelberg. pp 107-129.

- Leeb, R., Sagha H., Chavarriaga R., del R Millan J. (2010). Multimodal fusion of muscle and brain signals for a hybrid-BCI. *Conf Proc IEEE Eng Med Biol Soc 2010*: 4343-4346.
- Lemm, S., Blankertz B., Dickhaus T., and Müller K.R. (2011). Introduction to machine learning for brain imaging. *NeuroImage 56*: 387-399. doi: 10.1016/j.neuroimage.2010.11.004.
- Liang, N., and Bougrain L. (2012.) Decoding finger flexion from band-specific ECoG signals in humans. *Front Neurosci 6*: 91. doi:10.3389/fnins.2012.00091.
- Liao, L.-D., Chen, C.-Y., Wang, I.-J., Chen, S.-F., Li, S.-Y., Chen, B.-W., Chang, J.-Y., and Lin, C.-T. (2012). Gaming control using a wearable and wireless EEG-based brain-computer interface device with novel dry foam-based sensors. *J. Neuroengineering Rehabil. 9*, 5. doi:10.1186/1743-0003-9-5.
- Lim, J.H., Hwang H.J., Han C.H., Jung K.Y., Im C.H. (2013.) Classification of binary intentions for individuals with impaired oculomotor function: 'eyes-closed' SSVEP-based brain-computer interface (BCI). *J Neural Eng 10*: 026021. doi: 10.1088/1741-2560/10/2/026021.
- Lohse, K. R., Hilderman, C. G. E., Cheung, K. L., Tatla, S., and Van der Loos, H. F. M. (2014). Virtual reality therapy for adults post-stroke: a systematic review and meta-analysis exploring virtual environments and commercial games in therapy. *PLoS ONE 9*, e93318. doi:10.1371/journal.pone.0093318.
- Lopez-Gordo, M. A., Fernandez, E., Romero, S., Pelayo, F., and Prieto, A. (2012). An auditory brain-computer interface evoked by natural speech. *J. Neural Eng. 9*, 036013. doi:10.1088/1741-2560/9/3/036013.
- Lotte, F., Guan, C., and Ang K.K. (2009). Comparison of designs towards a subject-independent brain-computer interface based on motor imagery. *Conf Proc IEEE Eng Med Biol Soc 2010*: 4543-4546.
- Lu, C.W., Patil P.G., and Chestek C.A. (2012.) Current challenges to the clinical translation of brain machine interface technology. *Int Rev Neurobiol 107*: 137-160. doi:10.1016/B978-0-12-404706-8.00008-5.
- Malik, W.Q., Truccolo W., Brown E.N., Hochberg L.R. (2011). Efficient decoding with steady-state Kalman filter in neural interface systems. *IEEE Trans Neural Syst Rehabil Eng 19*: 25-34.
- Marshall, D., Coyle D., Wilson S., Callaghan M. (2013.) Games, gameplay, and BCI: the state of the art. *IEEE T Comp Intel AI 5*: 82-99.
- Maslen, H., Douglas, T., Cohen Kadosh, R., Levy, N., and Savulescu, J. (2014). The regulation of cognitive enhancement devices: extending the medical model. *J. Law Biosci. 1*, 68-93. doi:10.1093/jlb/lst003.
- Matsushita, K., Hirata, M., Suzuki, T., Ando, H., Ota, Y., Sato, F., Morris, S., Yoshida, T., Matsuki, H., Yoshimine, T (2013). Development of an implantable wireless ECoG 128ch recording device for clinical brain machine interface. *Conf Proc IEEE Eng Med Biol Soc 2013*: 1867-1870.

McCullagh, P., Ware, M., Mulvenna, M., Lightbody, G., Nugent, C., McAllister, G., Thomson, E., Martin, S., Mathews, S., Todd, D., et al. (2010). Can brain computer interfaces become practical assistive devices in the community? *Stud. Health Technol. Inform.* 160, 314–318.

McFarland D.J., Sarnacki W.A., Wolpaw .R. (2011). Should the parameters of a BCI translation algorithm be continually adapted? *J Neurosci Methods* 199: 103-107.

McFarland D.J., Sarnacki W.A., Wolpaw J.R. (2010). Electroencephalographic (EEG) control of three-dimensional movement. *J Neural Eng* 7: 036007. doi:10.1088/1741-2560/7/3/036007.

McGie, S. C., Nagai, M. K., and Artinian-Shaheen, T. (2013). Clinical ethical concerns in the implantation of brain-machine interfaces. *IEEE Pulse* 4, 32–37. doi:10.1109/MPUL.2013.2242014.

Mellinger J., Schalk G., Braun C., Preissl H., Rosenstiel W., Birbaumer N. Kübler A (2007). An MEG-based brain-computer interface (BCI). *NeuroImage* 36: 581–593.

Millán J. Del R., Mouriño J (2003). Asynchronous BCI and local neural classifiers: an overview of the Adaptive Brain Interface project. *IEEE Trans Neural Syst Rehabil Eng* 11, 159–161.

Millan, J. d. R., Rupp, R., Muller-Putz, G. R., Murray-Smith, R., Giugliemma, C., Tangermann, M., Vidaurre, C., Cincotti, F., Kubler, A., Leeb, R., et al. (2010). Combining Brain-Computer Interfaces and Assistive Technologies: State-of-the-Art and Challenges. *Front. Neurosci.* 4. doi:10.3389/fnins.2010.00161.

Moran D. (2010). Evolution of brain-computer interface: action potentials, local field potentials and electrocorticograms. *Curr Opin Neurobiol* 20: 1-5.

Mugler E.M., Patton J.L., Flint R.D., Wright Z.A., Schuele S.U., Rosenow ., Shih J.J., Krusienski D.J., Slutzky MW (2014) Direct classification of all American English phonemes using signals from functional speech motor cortex. *J Neural Eng* 11: 035015.

Mugler, J.P. (2014) Optimized three-dimensional fast-spin-echo MRI. *J Magn Res Imaging* 39: 745-767.

Müller-Putz, G.R., Breitwieser C., Cincotti F., Leeb R., Schreuder M., Leotta F., Tavella M., Bianchi L., Kreiling A., Ramsay A., Rohm M., Sagebaum M., Tonin L., Neuper C., Millán J. del R (2011). Tools for brain-computer interaction: A general concept for a hybrid BCI. *Front Neuroinform* 5: 30.

Nicolas-Alonso, L.F., Gomez-Gil J. (2012) Brain computer interfaces, a review. *Sensors* 12: 1211-1279.

Nijboer, F. (2013). Brain-Computer Interfaces – perspectives of stakeholders on technical, ethical, legal and social issues. *Ann. Phys. Rehabil. Med.* 56, e377–e378. doi:10.1016/j.rehab.2013.07.971.

Nijboer, F., Clausen J., Allison B.Z., Haselager P. (2013). The Asilomar survey: Stakeholders' opinions on ethical issues related to brain-computer interfacing. *Neuroethics* 6: 541-578.

Nijboer, F., Clausen, J., Allison, B. Z., and Haselager, P. (2013). The Asilomar Survey: Stakeholders' Opinions on Ethical Issues Related to Brain-Computer Interfacing. *Neuroethics* 6, 541–578. doi:10.1007/s12152-011-9132-6.

Nijboer, F., Plass-Oude Bos, D., Blokland, Y., van Wijk, R., and Farquhar, J. (2014). Design requirements and potential target users for brain-computer interfaces – recommendations from rehabilitation professionals. *Brain-Comput. Interfaces* 1, 50–61. doi:10.1080/2326263X.2013.877210.

Obrig., H., Steinbrink J. (2011). Non-invasive optical imaging of stroke. *Philos Trans A Math Phys Eng Sci* 369: 4470-4494.

Onaran, I., Ince N.F., Cetin A.E. (2011). Classification of multichannel ECoG related to individual finger movements with redundant spatial projections. *Conf Proc IEEE Eng Med Biol Soc* 2011: 5424-5427.

Orsborn, A.L., Carmena, J. (2013). Creating new functional circuits for action via brain-machine interface. *Front Comput Neurosci* 7: 157.

Orsborn, A.L., Dangi S., Moorman H.G., Carmena J.M. (2012). Closed-loop decoder adaptation on intermediate time-scales facilitates rapid BMI performance improvements independent of decoder initialization conditions. *IEEE Trans Neural Syst Rehabil Eng* 20: 468-477.

Owen, A.M. (2013). Detecting consciousness: unique role for neuroimaging. *Annu Rev Psychol* 64: 109-133.

Parikh, P.T., Sandhu G.S., Blackham K.A., Coffey M.D., Hsu D., Liu K., Jesberger J., Griswold M., Sunshine J.L. (2011). Evaluation of image quality of a 32-channel versus a 12 channel head coil at 1.5T for MR imaging of the brain. *AJNR Am J Neuroradiol* 32: 365-373.

Pfurtscheller, G., Allison B.Z., Brunner C., Bauernfeind G., Solis-Escalante T., Scherer R., Zander T.O., Müller-Putz G., Neuper C., Birbaumer N. (2010). The hybrid BCI. *Front Neurosci* 4: 1-11.

Plass-Oude Bos, D., Poel, M., and Nijholt, A. (2011). "A Study in User-Centered Design and Evaluation of Mental Tasks for BCI," in *Advances in Multimedia Modeling*, eds. K.-T. Lee, W.-H. Tsai, H.-Y. M. Liao, T. Chen, J.-W. Hsieh, and C.-C. Tseng (Berlin, Heidelberg: Springer Berlin Heidelberg), 122–134.

Pokorny, C., Klobassa, D. S., Pichler, G., Erlbeck, H., Real, R. G. L., Kübler, A., Lesenfants, D., Habbal, D., Noirhomme, Q., Riseti, M., et al. (2013). The auditory P300-based single-switch brain-computer interface: paradigm transition from healthy subjects to minimally conscious patients. *Artif. Intell. Med.* 59, 81–90. doi:10.1016/j.artmed.2013.07.003.

Riccio, A., Leotta, F., Bianchi, L., Aloise, F., Zickler, C., Hoogerwerf, E.-J., Kuebler, A., Mattia, D., and Cincotti, F. (2011). Workload measurement in a communication application operated through a P300-based brain-computer interface. *J. Neural Eng.* 8. doi:10.1088/1741-2560/8/2/025028.

Ritaccio, A., Boatman-Reich D., Brunner P., Cervenka M.C, Cole A.J., Crone N., Duckrow R., Korzeniewska A., Litt B., Miller K.J, Moran DW, Parvizi J, Williams J, Schalk G (2011) Proceedings of the second international workshop on advances in electrocorticography. *Epilepsy Behav* 22: 641-660.

- Rose, N. (2014). The Human Brain Project: social and ethical challenges. *Neuron* 82, 1212–1215. doi:10.1016/j.neuron.2014.06.001.
- Rouse, AG, Stanslaski SR, Cong P, Jensen RM, Afshar P, Ullestad D, Gupta R, Molnar GR, Moran DW, Denison TJ (2011) A chronic generalized bi-directional brain-machine interface. *J Neural Eng* 8 036018.
- Sabarigiri, B, Suganyadevi D (2014) Processing techniques for artifacts removal to improve the performance of electroencephalogram (EEG) features extraction. *Int J Innov Res Sci Eng Technol* 3: 2087-2092.
- Salomon, R, Darulova J, Narsude M, Van Der Zwaag W (2014) Comparison of an 8-Channel coil for high-resolution fMRI at 7T. *Brain Topogr* 27: 209-212.
- Samek W, Vidaurre C, Müller KR, Kawanabe M (2012) Stationary common spatial patterns for brain-computer interfacing. *J Neural Eng* 9: 026013.
- Sanchez, G, Daunizeau J, Maby E, Bertrand O, Bompas A, Mattout J (2014) Toward a new application of real-time electrophysiology: online optimization of cognitive neurosciences hypothesis testing. *Brain Sci* 4: 49-72.
- Sandrini, M., and Cohen, L. G. (2013). Noninvasive brain stimulation in neurorehabilitation. *Handb Clin Neurol* 116, 499–524. doi:10.1016/B978-0-444-53497-2.00040-1.
- Scherer, R., Lee, F., Schlogl, A., Leeb, R., Bischof, H., and Pfurtscheller, G. (2008). Toward self-paced brain-computer communication: navigation through virtual worlds. *IEEE Trans. Biomed. Eng.* 55, 675–682. doi:10.1109/TBME.2007.903709.
- Schermer, M. (2009). The Mind and the Machine. On the Conceptual and Moral Implications of Brain-Machine Interaction. *Nanoethics* 3, 217–230. doi:10.1007/s11569-009-0076-9.
- Schettini, F., Riccio, A., Simione, L., Liberati, G., Caruso, M., Frasca, V., Calabrese, B., Mecella, M., Pizzimenti, A., Inghilleri, M., et al. (In press). Assistive Device With Conventional, Alternative, and Brain-Computer Interface Inputs to Enhance Interaction With the Environment for People With Amyotrophic Lateral Sclerosis: A Feasibility and Usability Study. *Arch. Phys. Med. Rehabil.*
- Schomberg, V., and Rene (2011). *Towards Responsible Research and Innovation in the Information and Communication Technologies and Security Technologies Fields*. Rochester, NY: Social Science Research Network
- Schreuder, M, Hoehne J, Blankertz B, Haufe S, Dickhaus T, Tangermann M (2013) Optimizing event-related potential based brain-computer interfaces: a systematic evaluation of dynamic stopping methods. *J Neural Eng* 10: 036025.
- Schreuder, M., Riccio, A., Riseti, M., Dähne, S., Ramsay, A., Williamson, J., Mattia, D., and Tangermann, M. (2013). User-centered design in brain-computer interfaces-a case study. *Artif. Intell. Med.* 59, 71–80. doi:10.1016/j.artmed.2013.07.005.
- Schultz, AE, Kuiken TA (2011) Neural interfaces for control of upper limb prostheses: The state of the art and future possibilities. *PM R* 3: 55-67.
- Schwarz, DA, Lebedev MA, Hanson TL, Dimitrov DF, Lehew G, Melow J, Rajangam S, Subramanian V, Ifft PJ, Li Z, Rmakrishnan A, Tate A, Zhuang KZ, Nicolelis MA (2013)

Chronic, wireless recordings of large-scale brain activity in freely moving rhesus monkeys. *Nat Methods* 11: 670-676.

Sharma, A, Rieth L, Tathireddy P, Harrison R, Oppermann H, Klein M, Topper M, Jung E, Normann R, Clark G, Solzbacher F (2012) Evaluation of the packaging and encapsulation reliability in fully integrate, fully wireless 100 channel Utah Slant Electrode Array (USEA): Implications for long term functionality. *Sens Actuators A Phys* 188: 167-172.

Shih, J. J., Krusienski, D. J., and Wolpaw, J. R. (2012). Brain-Computer Interfaces in Medicine. *Mayo Clinic Proceedings* 87, 268–279. doi:10.1016/j.mayocp.2011.12.008.

Shih, JJ, Krusienski DJ, Wolpaw JR (2012) Brain-computer interfaces in medicine. *Mayo Clin Proc* 87: 268-279.

Silvoni, S., Ramos-Murguialday, A., Cavinato, M., Volpato, C., Cisotto, G., Turolla, A., Piccione, F., and Birbaumer, N. (2011). Brain-computer interface in stroke: a review of progress. *Clin EEG Neurosci* 42, 245–252.

Sitaram, R, Lee, S, Birbaumer N (2012) BCIs that use brain metabolic signals. In: *Brain-Computer Interfaces. Principles and Practice*. Wolpaw JR, Winter Wolpaw E (eds).

Sitaram, R, Zhang H, Guan C, Thulasidas M, Hoshi Y, Ishikawa A, Shimizu K, Birbaumer N (2007) Temporal classification of multichannel near-infrared spectroscopy signals of motor imagery for developing a brain-computer interface. *NeuroImage* 34: 1416–1427.

Song, H., Zhang D., Ling Z., Zuo H., and Hong B. (2012). High gamma oscillations enhance the subdural visual speller. *Conf Proc IEEE Eng Med Biol Soc* 2012: 1711-1714.

Speier, W, Fried I, Pouratian N (2013) Improved P300 speller performance using electrocorticography, spectral features, and natural language processing. *Clin Neurophysiol* 124: 1321-1328.

Thompson, DE, Blain-Moraes S, Huggins JE (2013) Performance assessment in brain-computer interface-based augmentative and alternative communication. *BioMed Eng OnLine* 12: 43.

Torres, Valderrama A, Oostenveld R, Vansteensel MJ, Huiskamp GM, Ramsey NF (2010) Gain of the human dura in vivo and its effects on invasive brain signal feature detection. *J Neurosci Methods* 187: 270-279.

Truelsen, T., Piechowski-Jóźwiak, B., Bonita, R., Mathers, C., Bogousslavsky, J., and Boysen, G. (2006). Stroke incidence and prevalence in Europe: a review of available data. *Eur J Neurol* 13, 581–598. doi:10.1111/j.1468-1331.2006.01138.x.

Truelsen, T., Piechowski- Jóźwiak, B., Bonita, R., Mathers, C., Bogousslavsky, J., and Boysen, G. (2006). Stroke incidence and prevalence in Europe: a review of available data. *Eur J Neurol*, 13(6), 581-598.

Van der Zwaag, W, Francis S, Head K, Peters A, Gowland P, Morris P, Bowtell R (2009) fMRI at 1.5, 3 and 7T: characterising BOLD signal changes. *Neuroimage* 47: 1425-14.

Vansteensel, MJ, Hermes D, Aarnoutse EJ, Bleichner MG, Schalk G, van Rijen PC, Leijten FS, Ramsey NF (2010) Brain-computer interfacing based on cognitive control. *Ann Neurol* 67: 809-816.

- Velliste, M, Perel S, Spalding MC, Whitford AS, Schwartz AB (2007) Cortical control of a prosthetic arm for self-feeding. *Nature* 453: 1098-1101.
- Vidaurre, C, Kawanabe M, Von Bünau P, Blankertz B, Müller KR (2011) Toward unsupervised adaptation of LDA for brain-computer interfaces. *IEEE Trans Biomed Eng* 58:, 587-597.
- Volosyak, I, Valbuena D, Malechka T, Peuscher J, Graser A (2010). Brain-computer interface using water-based electrodes. *J Neural eng* 7: 066007.
- Wang, J, He L, Zheng H, Lu Z-L (2014) Optimizing the magnetization-prepared rapid gradient-echo (MP-rage) sequence. *PLoS ONE* 9: e96899.
- Wang, W., Collinger J.L., Degenhart A.D., Tyler-Kabara E.C., Schwartz A.B., Moran D.W., Weber D.J., Wodlinger B., Vinjamuri R.K., Ashmore R.C., Kelly J.W., Boninger M.L. (2013). An electrocorticographic brain interface in an individual with tetraplegia. *PLoS One* 8: e55344. doi:10.1371/journal.pone.0055344.
- Wang, Y., Gao X., Hong B., Jia C., Gao S. (2008). Brain-computer interfaces based on visual evoked potentials. *IEEE Eng Med Biol Mag*, 27: 64-71.
- Weiskopf, N (2012). Real-time fMRI and its application to neurofeedback. *NeuroImage* 62: 682-692.
- Wilson, J.J, and Palaniappan R. (2011). Analogue mouse pointer control via an online steady state visual evoked potential (SSVEP) brain-computer interface. *J Neural Eng* 8: 025026.
- Wolpaw JR and Wolpaw EW (2012). Brain-computer interfaces: something new under the sun. In: Wolpaw JR, Wolpaw EW. *Brain-computer interfaces: principles and practice*, pp. 3-12, Oxford University Press, New York.
- Wolpaw, J., and Wolpaw, E. W. (2012). *Brain-Computer Interfaces: Principles and Practice*. Oxford University Press.
- Wolpaw, J.R., Wolpaw E.W. (eds) (2012.) *Brain-computer interfaces: Principles and practice*. Oxford: Oxford Univ. Press.
- World Health Organization Statistics Report (2012).
- Yin, M., Li H., Bull C., Borton D.A., Aceros J., Larson L., and Nurmikko A.V. (2013). An externally head-mounted wireless neural recording device for laboratory animal research and possible human clinical use. *Conf Proc IEEE Eng Med Biol Soc* 2013: 3109-3114.
- Yuan, P., Gao X., Allison B., Wang Y., Bin G., and Gao S. (2013). A study of the existing problems of estimating the information transfer rate in online brain-computer interfaces. *J Neural Eng* 10: 26014. doi:10.1088/1741-2560/10/2/026014.
- Zhang, D., Song H., Xu R., Zhou W., Ling Z., and Hong B. (2013). Toward a minimally invasive brain-computer interface using a single subdural channel: a visual speller study. *NeuroImage* 71: 30-41. doi:10.1016/j.neuroimage.2012.12.069.
- Zhang, Y, Xu P, Liu T, Hu J, Zhang R, and Yao D (2012). Multiple frequencies sequential coding for SSVEP-based brain computer interface. *PloS ONE* 7: e29519. doi:10.1371/journal.pone.0029519.

Zickler, C., Halder, S., Kleih, S. C., Herbert, C., and Kübler, A. (2013). Brain Painting: usability testing according to the user-centered design in end users with severe motor paralysis. *Artif. Intell. Med.* 59, 99–110. doi:10.1016/j.artmed.2013.08.003.

Zickler, C., Riccio, A., Leotta, F., Hillian-Tress, S., Halder, S., Holz, E., Staiger-Sälzer, P., Hoogerwerf, E.-J., Desideri, L., Mattia, D., et al. (2011). A brain-computer interface as input channel for a standard assistive technology software. *Clin. EEG Neurosci. Off. J. EEG Clin. Neurosci. Soc. ENCS* 42, 236–244.